

SONIFEX

RB-DAC1
Digital To Analogue Converter

Catalogue ²⁰¹⁶





RB-DAC1 Digital To Analogue Converter

Using 24 bit, 192kHz capable devices, the RB-DAC1 D/A Converter is a 1U rack-mount which produces a stereo balanced XLR or unbalanced phono output from an incoming AES/EBU or S/PDIF digital input signal. There is also a headphone output with volume control for monitoring purposes.

The analogue outputs have an output level control, allowing full-scale settings selectable from +12dBu, +18dBu or +24dBu. The RCA phono outputs have a further 8.5dBu attenuation incorporated.

There is a button to select either the AES/EBU or S/PDIF input for the D/A converter, which is located on the rear panel.

Additionally, if de-emphasis is selected, the RB-DAC1 will decode 50/15µs emphasis when indicated by certain channel status bits in the incoming digital audio data.

When operating, the front panel power LED flashes whenever the unit is not synchronised to the incoming digital signal.



Category: Digital Audio Converters.
Product Function: Converts a digital audio signal to an analogue signal.

Typical Applications: To connect the output of a CD player to an analogue amplifier, or the program output of a digital mixer to a pair of powered speakers.

Features: AES/EBU & S/PDIF digital inputs, headphone amplifier, configurable full-scale settings.

Specification For RB-DAC1

Audio Specification

Maximum Output Level:	+24dBu balanced, +14dBu unbalanced +12dBu headphone
Output Impedance:	<50Ω balanced, <75Ω unbalanced
Dynamic Range:	>100dB
Gain Range:	Selectable 12dBu, 18dBu or 24dBu output level, ref FSD
Headphone Output:	Drives 150mW into 32Ω to 600Ω professional headphones
Distortion & Noise:	<0.01% THD + N @1kHz, ref 0dBu
Sample Freq. Range:	32kHz - 192kHz

Operational Controls

Digital Input Select:	AES/EBU or S/PDIF, via push-button
-----------------------	------------------------------------

Gain Select:	DIP switch
De-emphasis On/Off:	DIP switch
Connections	
Digital Inputs:	1 x AES/EBU XLR 3 pin female 1 x S/PDIF RCA phono
Analogue Outputs:	2 x XLR 3 pin male (balanced) 2 x RCA phono (unbalanced)
Headphone Output:	1 x ¼" (6.35mm) A/B-gauge 3-pole stereo jack sockets
Mains Input:	Filtered IEC, 110V-120V, or 220-240V, fused, 10W max
Fuse Rating:	Anti-surge fuse 100mA 20 x 5mm (230VAC) Anti-surge fuse 250mA 20 x 5mm (115VAC)

Equipment Type

RB-DAC1:	Digital to analogue converter
----------	-------------------------------

Physical Specification

Dimensions (Raw):	48cm (W) x 10.8cm (D) x 4.2cm (H) (1U) 19" (W) x 4.3" (D) x 1.7" (H) (1U)
Dimensions (Boxed):	58.5cm (W) x 22.5cm (D) x 7cm (H) 23" (W) x 8.9" (D) x 2.8" (H)
Weight:	Nett: 1.4kg Gross: 2.0kg Nett: 3.1lbs Gross: 4.4lbs



SONIFEX

www.sonifex.co.uk

UK Office:

Sonifex Ltd

61 Station Road, Irthlingborough,

Northants, NN9 5QE, UK

Tel: +44 (0) 1933 650700

Fax: +44 (0) 1933 650726

Email: sales@sonifex.co.uk

Australian Office:

Sonifex Pty Ltd

12/6 Leighton Place,

Hornsby NSW 2077, Australia

Tel: +61 (2) 9987 0499

Fax: +61 (2) 9476 4950

Email: sales@sonifex.com.au